

## C0603X360GATACTU

Aliases (C0603X360GATAC7867)

**Specifications** 

Insulation Resistance

SMD Comm X8G HT150C Flex, Ceramic, 36 pF, 2%, 250 VDC, X8G, SMD, MLCC, High Temperature, Ultra-Stable, 0603, 0.4 mm



| General Information      |  |
|--------------------------|--|
| Series                   | SMD Comm X8G HT150C Flex                     |
| Style                    | SMD Chip                                     |
| Description              | SMD, MLCC, High Temperature,<br>Ultra-Stable |
| Features                 | High Temperature, Ultra-Stable               |
| RoHS                     | Yes  |
| Termination              | Flexible Termination                         |
| Marking                  | No   |
| AEC-Q200                 | No   |
| Typical Component Weight | 4.6 mg                                       |
| Shelf Life               | 78 Weeks                                     |
| MSL                      | 1  |

| Dimensions |                  |
|------------|------------------|
| Chip Size  | 0603             |
| L          | 1.6mm +/-0.17mm  |
| W          | 0.8mm +/-0.15mm  |
| Т          | 0.8mm +/-0.15mm  |
| S          | 0.4mm MIN        |
| В          | 0.45mm +/-0.15mm |
|            |                  |

| Capacitance  | 36 pF  |
|--|--|
| Measurement Condition  | 1 MHz 1.0Vrms                                      |
| Tolerance  | 2%   |
| Voltage DC   | 250 VDC  |
| Dielectric Withstanding Voltage  | 625 VDC  |
| Temperature Range  | -55/+150°C   |
| Temp. Coefficient  | X8G  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC) | 30 ppm/C, 1MegaHz 1.0Vrms                          |
| Dissipation Factor   | 0.1% 1 MHz 1.0Vrms                                 |
| Aging Rate   | 0% Loss/Decade Hour: Referee<br>Time is 1000 Hours |

100 GOhms

| Packaging Specifications |                        |
|--------------------------|------------------------|
| Packaging                | T&R, 180mm, Paper Tape |
| Packaging Quantity       | 4000                   |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/05/2025 © 2006 - 2025 YAGEO