

C1210C271FATACTU

Aliases (C1210C271FATAC7800)

SMD Comm X8G HT150C, Ceramic, 270 pF, 1%, 250 VDC, X8G, SMD, MLCC, High Temperature, Ultra-Stable, 1210, 1.5 mm



General Information	
Series	SMD Comm X8G HT150C
Style	SMD Chip
Description	SMD, MLCC, High Temperature, Ultra-Stable
Features	High Temperature, Ultra-Stable
RoHS	Yes
Termination	Tin
Marking	No
AEC-Q200	No
Typical Component Weight	30 mg
Shelf Life	78 Weeks
MSL	1

Dimensions	
Chip Size	1210
L	3.2mm +/-0.2mm
W	2.5mm +/-0.2mm
Т	0.78mm +/-0.10mm
S	1.5mm MIN
В	0.5mm +/-0.25mm

VV	2.5mm +/-0.2mm	
Т	0.78mm +/-0.10mm	
S	1.5mm MIN	
В	0.5mm +/-0.25mm	
Packaging Specifications		

4000

Packaging

Packaging Quantity

Specifications		
Capacitance	270 pF	
Measurement Condition	1 MHz 1.0Vrms	
Tolerance	1%	
Voltage DC	250 VDC	
Dielectric Withstanding Voltage	625 VDC	
Temperature Range	-55/+150°C	
Temp. Coefficient	X8G	
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C, 1MegaHz 1.0Vrms	
Dissipation Factor	0.1% 1 MHz 1.0Vrms	
Aging Rate	0% Loss/Decade Hour: Referee Time is 1000 Hours	
Insulation Resistance	100 GOhms	

2.00.patio acto.
Aging Rate
Insulation Resistance

T&R, 180mm, Plastic Tape

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/10/2025 © 2006 - 2025 YAGEO