

## C1812C275K5RACTU

**Specifications** 

Insulation Resistance

Aliases (C1812C275K5RAC7800) SMD Comm X7R, Ceramic, 2.7 uF, 10%, 50 VDC, X7R, SMD, MLCC, Temperature Stable, Class II, 1812, 2.3 mm



| General Information      |  |
|--------------------------|--|
| Series                   | SMD Comm X7R                               |
| Style                    | SMD Chip                                   |
| Description              | SMD, MLCC, Temperature<br>Stable, Class II |
| Features                 | Temperature Stable, Class II               |
| RoHS                     | Yes  |
| Termination              | Tin  |
| Marking                  | No   |
| AEC-Q200                 | No   |
| Typical Component Weight | 185 mg                                     |
| Shelf Life               | 78 Weeks                                   |
| MSL                      | 1  |

| Dimensions |                 |
|------------|-----------------|
| Chip Size  | 1812            |
| L          | 4.5mm +/-0.3mm  |
| W          | 3.2mm +/-0.3mm  |
| Т          | 1.7mm +/-0.15mm |
| S          | 2.3mm MIN       |
| В          | 0.6mm +/-0.35mm |
|            |                 |

| Capacitance  | 2.7 uF   |
|--|--|
| Measurement Condition  | 1 kHz 1.0Vrms                                      |
| Tolerance  | 10%  |
| Voltage DC   | 50 VDC   |
| Dielectric Withstanding Voltage  | 125 VDC  |
| Temperature Range  | -55/+125°C   |
| Temp. Coefficient  | X7R  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC) | 15%, 1kHz 1.0Vrms                                  |
| Dissipation Factor   | 2.5% 1 kHz 1.0 Vrms                                |
| Aging Rate   | 3% Loss/Decade Hour: Referee<br>Time is 1000 Hours |
|  |  |

185.2 MOhms

| Packaging Specifications |                          |
|--------------------------|--------------------------|
| Packaging                | T&R, 180mm, Plastic Tape |
| Packaging Quantity       | 1000                     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 04/30/2025 © 2006 - 2025 YAGEO