


## C1812X153M2TACTU

Aliases (C1812X153M2TAC7800)

SMD Comm X8G HT150C Flex, Ceramic, 0.015 uF, 20%, 200 VDC, X8G, SMD, MLCC, High Temperature, Ultra-Stable, 1812, 2.3 mm



| General Information      |  |
|--------------------------|--|
| Series                   | SMD Comm X8G HT150C Flex                     |
| Style                    | SMD Chip                                     |
| Description              | SMD, MLCC, High Temperature,<br>Ultra-Stable |
| Features                 | High Temperature, Ultra-Stable               |
| RoHS                     | Yes  |
| Termination              | Flexible Termination                         |
| Marking                  | No   |
| AEC-Q200                 | No   |
| Typical Component Weight | 67 mg  |
| Shelf Life               | 78 Weeks                                     |
| MSL                      | 1  |

| Dimensions |                 |
|------------|-----------------|
| Chip Size  | 1812            |
| L          | 4.5mm +/-0.4mm  |
| W          | 3.2mm +/-0.3mm  |
| Т          | 1mm +/-0.10mm   |
| S          | 2.3mm MIN       |
| В          | 0.7mm +/-0.35mm |
|            |                 |

| В                        | 0.7mm +/-0.35mm          |
|--------------------------|--------------------------|
|                          |                          |
| Packaging Specifications |                          |
| Packaging                | T&R, 180mm, Plastic Tape |

1000

Packaging Quantity

| Specifications   |  |
|--|--|
| Capacitance  | 0.015 uF   |
| Measurement Condition  | 1 kHz 1.0Vrms                                      |
| Tolerance  | 20%  |
| Voltage DC   | 200 VDC  |
| Dielectric Withstanding Voltage  | 500 VDC  |
| Temperature Range  | -55/+150°C   |
| Temp. Coefficient  | X8G  |
| Capacitance Change with<br>Reference to +25°C and 0 VDC<br>Applied (TCC) | 30 ppm/C, 1kHz 1.0Vrms                             |
| Dissipation Factor   | 0.1% 1 kHz 1.0Vrms                                 |
| Aging Rate   | 0% Loss/Decade Hour: Referee<br>Time is 1000 Hours |
| Insulation Resistance  | 66.6667 GOhms                                      |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/03/2025 © 2006 - 2025 YAGEO