

C1825C183JFRACTU

Aliases (C1825C183JFRAC7800)

SMD Comm X7R HV, Ceramic, 0.018 uF, 5%, 1,500 VDC, X7R, SMD, MLCC, High Voltage, Temperature Stable, 1825, 2.3 mm



| General Information | | |
|--------------------------|--|--|
| Series | SMD Comm X7R HV | |
| Style | SMD Chip | |
| Description | SMD, MLCC, High Voltage, Temperature Stable | |
| Features | High Voltage | |
| RoHS | Yes | |
| Termination | Tin | |
| Marking | No | |
| AEC-Q200 | No | |
| Typical Component Weight | 280 mg | |
| Shelf Life | 78 Weeks | |
| MSL | 1 | |

0.018 uF

| Dimensions | |
|------------|-----------------|
| Chip Size | 1825 |
| L | 4.5mm +/-0.3mm |
| W | 6.4mm +/-0.4mm |
| Т | 1.6mm +/-0.20mm |
| S | 2.3mm MIN |
| В | 0.6mm +/-0.35mm |
| | |

Packaging Packaging Packaging (

| | 6.4mm +/-0.4mm | Tolerance | 5% |
|------------------|--------------------------|---|------------------------------|
| | 1.6mm +/-0.20mm | Voltage DC | 1500 VDC |
| | 2.3mm MIN | Dielectric Withstanding Voltage | 1,800 VDC |
| | 0.6mm +/-0.35mm | Temperature Range | -55/+125°C |
| | | Temp. Coefficient | X7R |
| g Specifications | | Capacitance Change with | 15%, 1kHz 1.0Vrms |
| J | T&R, 180mm, Plastic Tape | Reference to +25°C and 0 VDC Applied (TCC) | |
| g Quantity | 1000 | Dissipation Factor | 2.5% 1 kHz 1.0 Vrms |
| | | Aging Rate | 3% Loss/Decade Hour: Referee |

Specifications

Capacitance

| 4.5mm +/-0.3mm | Measurement Condition | 1 kHz 1.0Vrms |
|--------------------------|--|--|
| 6.4mm +/-0.4mm | Tolerance | 5% |
| 1.6mm +/-0.20mm | Voltage DC | 1500 VDC |
| 2.3mm MIN | Dielectric Withstanding Voltage | 1,800 VDC |
| 0.6mm +/-0.35mm | Temperature Range | -55/+125°C |
| | Temp. Coefficient | X7R |
| T&R, 180mm, Plastic Tape | Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms |
| 1000 | Dissipation Factor | 2.5% 1 kHz 1.0 Vrms |
| | Aging Rate | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| | Insulation Resistance | 55.5556 GOhms |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/04/2025 © 2006 - 2025 YAGEO