



KC-LINK Auto COG, Ceramic, 0.082 uF, 5%, 500 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, Automotive Grade, 2220



General Information	
Series	KC-LINK Auto COG
Style	SMD Chip
Description	SMD, MLCC, FT-CAP, Ultra- Stable, Automotive Grade
Features	FT-CAP, Ultra-Stable, Automotive Grade
RoHS	Yes
Termination	Flexible Termination
Marking	No
Qualifications	AEC-Q200
AEC-Q200	Yes
Typical Component Weight	260 mg
Shelf Life	78 Weeks
MSL	1

0.082 uF

Dimensions			
Chip Size	2220		
L	5.9mm +/-0.75mm		
W	5mm +/-0.4mm		
Т	2mm +/-0.20mm		
В	0.7mm +/-0.35mm		
Packaging Specifications			

	5.9mm +/-0.75mm	Measurement Condition	1 kHz 1.0Vrms	
	5mm +/-0.4mm	Tolerance	5%	
	2mm +/-0.20mm	Voltage DC	500 VDC	
0.7mm +/-0.35mm		Dielectric Withstanding Voltage	750 VDC	
		Temperature Range	-55/+150°C	
ıs		Temp. Coefficient	COG	
T&R, 180mm, Plastic Tape 500	Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C, 1kHz 1.0Vrms		
		Dissipation Factor	0.1% 1 kHz 1.0Vrms	
		Aging Rate	0% Loss/Decade Hour	

Specifications Capacitance

W	5mm +/-0.4mm	Tolerance	5%
Т	2mm +/-0.20mm	Voltage DC	500 VDC
В	0.7mm +/-0.35mm	Dielectric Withstanding Voltage	750 VDC
		Temperature Range	-55/+150°C
Packaging Specifications		Temp. Coefficient	COG
Packaging	T&R, 180mm, Plastic Tape	Capacitance Change with	30 ppm/C, 1kHz 1.0Vrms
Packaging Quantity	500	Reference to +25°C and 0 VDC Applied (TCC)	
		Dissipation Factor	0.1% 1 kHz 1.0Vrms
		Aging Rate	0% Loss/Decade Hour
		Insulation Resistance	12.1951 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/12/2025 © 2006 - 2025 YAGEO








KC-LINK Auto COG, Ceramic, 0.082 uF, 5%, 500 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, Automotive Grade, 2220


Simulations


For the complete simulation environment please visit K-SIM.











Generated 05/12/2025 © 2006 - 2025 YAGEO



CKC21X823JCGACAUTO

KC-LINK Auto COG, Ceramic, 0.082 uF, 5%, 500 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, Automotive Grade, 2220

These are simulations.

This is not a specification!

The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

The responses shown do not represent a specified or implied maximum capability of the device for all applications.

- The ESR used for ripple "Ripple Current/Voltage vs. Frequency" plots is the ESR at ambient temperature.

- The ESR used for ripple Ripple Currenty votage vs. rrequency plots is adjusted to each incremental temperature rise before the power and ripple current is calculated.
 The ESR in the "Temperature Rise vs. Ripple Current" plots is adjusted to each incremental temperature rise before the power and ripple current is calculated.
 The effects shown herein are based on measured data from a multiple part sample of the parts in question.
 Ripple capability of this device will be factored by thermal resistance (Rth) created by circuit traces (addi affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.
 The peak voltages generated in the "Temperature Rise vs. Combined Ripple Currents" plot are calculated for each frequency and are not combined with voltages
- generated at any other harmonics.

 Please consult with the catalog or field applications engineer for maximum capability of the device in specific applications.

All product information and data (collectively, the "Information") are subject to change without notice.

KEMET K-SIM is designed to simulate behavior of components with respect to frequency, ambient temperature, and DC bias levels. The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation effects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

All Information given herein is believed to be accurate and reliable, but is presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

If you have any questions please contact K-SIM.

Generated 05/12/2025 © 2006 - 2025 YAGEO