

LDECC2220KA5N00

Aliases (DECC2220KA5N00)

LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.022 uF, 10%, 50 VDC, 40 VAC, 125°C, 1812, 1.7 mm


LDE

Yes

SMD Chip

Metallized PEN Stacked

Automotive Grade



// † `		
Т	Qualifications	AEC-Q200
	AEC-Q200	Yes
	Typical Component Weight	0.175 g
	Shelf Life	104 Weeks
_ p	MSL	3

General Information

Series Dielectric

Style

RoHS

Features

Click here for the 3D model.

Dimensions	
Chip Size	1812
L	4.7mm +0.3/-0.2mm
W	3.3mm +/-0.3mm
Т	1.7mm MAX
В	0.4mm +0.5/-0.3mm
Packaging Specifications	
Packaging	T&R

Packaging Quantity

4000

_		
Specifications		
Capacitance	0.022 uF	
Tolerance	10%	
Voltage DC	50 VDC	
Voltage AC	40 VAC	
Temperature Range	-55/+125°C	
Rated Temperature	125°C	
Dissipation Factor	0.8% 1kHz	
Insulation Resistance	1GOhms	
Max dV/dt	100 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 04/24/2025 © 2006 - 2025 YAGEO