



Note: '('') correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

General Information

| | |
|--------------------------|---|
| Series | PEG228 |
| Dielectric | Aluminum Electrolytic |
| Style | Axial |
| Description | Vibration Resistant Ultra High CV Aluminum Electrolytic |
| RoHS | Yes |
| Lead | Wire Leads |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Halogen Free | Yes |
| Typical Component Weight | 13 g |
| Shelf Life | 156 Weeks |

Specifications

| | |
|-------------------|--|
| Capacitance | 2,200 uF |
| Tolerance | -10/+30% |
| Voltage DC | 40 VDC |
| Temperature Range | -40/+150°C |
| Rated Temperature | 150°C |
| Life | 8400 Hrs (Rated Voltage At 125C), 2000 Hrs (Rated Voltage At 150C) |
| ESR | 44 mOhms (100Hz 20C), 20 mOhms (100kHz 20C), 10.2 mOhms (5-100kHz 150C) |
| Ripple Current | 22.6 Amps (5kHz 125C, With Heat Sink), 14.3 Amps (5kHz 140C, With Heat Sink), 6.4 Amps (5kHz 150C, With Heat Sink), 7.4 Amps (5kHz 125C), 9.3 Amps (5kHz 125C Max) |
| Leakage Current | 268 uA (5min 20°C) |

Dimensions

| | |
|----|-----------------|
| D | 20.2mm +/-0.5mm |
| L | 26.7mm +/-1mm |
| L1 | 33mm MIN |
| LL | 40mm +/-2mm |
| F | 1mm +/-0.03mm |

Packaging Specifications

| | |
|-----------|-----------|
| Packaging | Bulk, Box |
|-----------|-----------|