


## T350A685K006AS7301

Aliases (T350A685K006ASTR) T350, Tantalum, MnO2 Tantalum, Commercial Grade, 6.8 uF, 10%, 6.3 VDC, Radial, Solid Tantalum, Conformal, Dipped, 2.54 mm



Click here for the 3D model.

General Information	
Series	T350
Dielectric	MnO2 Tantalum
Style	Radial
Description	Radial, Solid Tantalum, Conformal, Dipped
Features	Low Leakage
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov /
SCIP Number	0c1392c3-c7b9-4178-827c-fa2 6617a3178
Termination	Lead (SnPb)
AEC-Q200	No
Construction	Conformal
Notes	Longest Lead Is Positive.

Dimensions	
D	4.5mm
н	7.1mm
S	2.54mm +/-0.38mm
F	0.5mm +/-0.05mm

1500

## SpecificationsCapacitance6.8 uFTolerance10%Voltage DC6.3 VDC (85C), 4 VDC (125C),<br/>0.063 VDC (125C Reverse)Temperature Range-55/+125°CDissipation Factor5%Leakage Current0.5 uA

F	0.5mm +/-0.05mm
Packaging Specifications	
Packaging	T&R, 305mm

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

**Packaging Quantity**